

**ACESEAL**

*Wetmate N'*  
*Stainproof*



Ref: AAIP/L/TDS/054-16

Rev: 02/05-16



A premium penetrating breathable sealer cum natural look enhancer which has an excellent stain inhibiting properties along with long lasting wet look for highly porous tiles or stones. It penetrates deep in to the surface and therefore has an extremely long-lasting effect. It is a fluoropolymer based sealer which penetrates and forms an invisible barrier. It makes the surface not only resist water but also dirt and other contaminants and make it easier to clean.

**ADVANTAGES:**

- Highly effective, Fluoropolymer based
- Long lasting wet look appearance, enhances the natural look
- User friendly, easy to apply by brush or roller
- Resists stains from water based contaminants
- Weather resistance, protects ancient structures, stone, bricks and tile
- Allow moisture vapor transmission
- UV resistant, Non-yellowing

**USES:**

- Interior and exterior, wall or floor application for residential and commercial use
- Can be applied on all kind of porous tiles or natural stones like Marbles, Granites, Flamed stones, Sand stones, etc

**AVAILABLE PACK SIZE:**

Available in 1 ltr, 5 ltr and 20 ltr packing

**SHELF LIFE:**

12 months, if stored in cool and dry area in unopened containers, protected from sun light. Shelf life is calculated from the month of manufacturing of the product.

**SURFACE PREPARATION:**

All dirt, dust, debris, oil, grease and old paint should be removed. All clean and dry surfaces is essential for the best results. Begin with a sound, clean, dry and roughened, oil-free application surface, as it is essential to the success and performance of this product. Spot test on surface can be conducted by applying the compound to a small, clean test area.

**APPLICATION PROCEDURE:**

- Mix the container well before application
- Apply Ace Seal Wetmate N' Stainproof uniformly over the surface by using a clean white cloth or paint brush
- Leave the surface 2-3 minutes and remove excess product from the surface using clean white cloth (Buffing).
- The removing/buffing should be done before the liquid dries on the surface. Drying may vary depending on temperature and porosity of the surface
- In case any dried residue is left on the surface, the same can be removed by reapplication of Ace Seal Wetmate N' Stainproof and cleaning the excess immediately
- Second coat can applied after 3 hours of first coat. Following same method for second coat application, but on opposite direction
- Multiple applications may be required for some stones
- Allow cure time of 24 hours for sealers to become completely effective.

**PROTECTION OF JOB SITE AND  
TIME TO CURE:**

Generally, Ace Seal Wetmate N' Stainproof will completely cure and perform in 24 hours. Protect the treated substrate or surface to cure for 24 hours before installation or exposure to dust, dirt and water or stain contact

**COVERAGE:**

Approximately 100 sft / 1ltr for two coats. Coverage will vary depending upon porosity and absorption capacity of the surface.

**EASY MAINTENANCE:**

It is very easy to maintain the treated area. It can be washed with clean water to remove dirt or dust.

**CAUTION:**

Avoid contact with eyes or skin. In case of contact, clean with plenty of water and seek medical attention. Use personal protective equipments such as gloves, goggles, aprons, masks, etc while handling the product and application of same

**LIMITATIONS:**

- It is not recommended to use on surface where continuous temperature exposure above 100°C.
- It is recommended that the complete installation should be cured 24 hours prior to installation or exposure.
- Should be tested and confirmed for performance or slight colour changes when used with porous, absorptive, textured surface
- Not recommended in some manufacturing facilities where heavy chemicals are used. Consult Technical Services on questionable installations.
- Colours may be slightly different than shown. When colour considerations are critical, a mock-up should be constructed prior to final application.

**CUSTOMER SERVICE:**

For any query related to product availability, cost, coverage, applicators, installation instructions, problems and trouble shooting, contact customer service executive on our 24 X 7 customer help line +91 963 260 5577 or write email to [customercare@acebond.in](mailto:customercare@acebond.in)

For product or other information, please write us to [info@acebond.in](mailto:info@acebond.in)

Visit us at [www.acebond.in](http://www.acebond.in)

**WARRANTY:**

Acrete Adhesions India Pvt Limited warrants to the original purchaser that its product shall be free from defects in material for a period of one year from the manufacturing of the product. Our sole liability under this warranty shall be limited to the replacement of our purchased product if proved defective under normal handling as stated in the TDS. This warranty will not extend to any other product or items which were handled along with our product. This warranty or any other legal issues or claims are subject to Mangalore jurisdiction only.

**DECLARATION:**

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided since conditions of use, application method and surface preparation at site are beyond our control. All legal issues are subject to Mangalore jurisdiction only.  
NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.