

# **ACEFIX**

## *Acrylic Crack filler*



Ref: AAIPL/TDS/058-16  
Rev: 02/05-16



High performance acrylic based crack filler paste used for sealing or repairing internal and external cracks in plasters or masonry surfaces. It is a highly flexible yet tough, non-shrink crack filler used to fill cracks up to 5mm. It has very good adhesion property over all type of plastered wall or masonry works.

### **ADVANTAGES:**

- Single component, white in colour, smooth finish
- Useful in minor expansion & contraction joints
- Low shrinkage, non-staining
- No cracking or crumbling
- Can be used on damp surface, structure in damp condition

### **APPLICATION**

Used for internal and external plastered brick masonry wall for cracks up to 5mm width.

### **AVAILABLE PACK SIZE:**

Available in 500gm and 1kg pack

### **STORAGE AND HANDLING:**

Store in cool and dry area in unopened original container

**SHELF LIFE:**

12 months if stored in cool and dry area in unopened container. Shelf life is calculated from the month of manufacturing of the product.

**CAUTION:**

- Store in cool and dry place.
- High temperature or moisture will affect the product.
- Once bottle is opened, then finish it off without keeping for long time.
- Avoid eye contact or prolonged contact with skin.
- Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes and consult a physician.
- Do not breathe directly; wear PPE whenever necessary

**WARRANTY**

Acrete adhesions India Private Limited warrants to the original purchaser that its product shall be free from defects in material for a period of one year from the manufacturing of the product. Our sole liability under this warranty shall be limited to the replacement of our purchased product if proved defective under normal handling as stated in the TDS. This warranty will not extend to any other product or items which were handled along with our product. This warranty or any other legal issues or claims are subject to Mangalore jurisdiction only.

**CUSTOMER SERVICE:**

For any query related to product availability, cost, coverage, applicators, installation instructions, problems and trouble shooting, contact customer service executive on our 24 X 7 customer help line +91 963 260 5577 or write email to [customercare@acebond.in](mailto:customercare@acebond.in)

For product or other information, please write us to [info@acebond.in](mailto:info@acebond.in)

Visit us at [www.acebond.in](http://www.acebond.in)

**DECLARATION:**

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided since conditions of use, method of application and surface preparation at site are beyond our control. All legal issues are subject to Mangalore jurisdiction only.

**NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.**