

ACEMIX

Grout Admix



Superior quality admix
for cementitious grouts



ACEMIX Grout admix is a high quality, milky white, latex based additive designed for use with ACEGROUT/AQUAPROOF Cementitious grout. ACEMIX Grout Admix is used in place of water to provide flexibility to the system after curing.

ADVANTAGES:

- Improves flexibility, resists powdering and cracking
- Gives hydrophobic property to the grout.
- Prevents damage to grouts from weathering and thermal shock.
- Reduces staining and water absorption

APPLICATIONS:

Suitable for mixing with Acegrout/Aquaproof series cementitious grouts

AVAILABLE PACK SIZE:

Available in 200ml, 400ml, 5 ltr and 20 ltr pack size.

SHELF LIFE:

36 months, if stored in cool and dry area in unopened bag. Shelf life is calculated from the month of manufacturing of the product.

MIXING PROCEDURE:

Use approximately 200ml of Acemix Grout Admix for 1 kg of Acegrout/Aquaproof coarse series grout powder and 400ml of Acemix Grout Admix for 1 kg of Acegrout/Aquaproof Superfine series grout powder. Take Acemix Grout Admix in a clean mixing container and add grout powder slowly. Mix by hand or with a slow speed mixer to a smooth stiff consistency. Allow to slake for 5-10 minutes and remix.

APPLICATION PROCEDURE:

Dampen tile surface with water. Spread with a sharp, firm rubber grout float. Work the grout paste into the joints until completely filled. Use diagonal strokes to pack the joints. Ensure that joint is filled and grout is not just sitting on top (i.e. “bridging the joint”).

REMOVAL OF EXCESS GROUT:

Remove excess grout by holding grout float at 70° to 90° angle and pulling the float diagonally across the grout joints.

Removing as much material as possible will make final cleaning easier. Allow joint to set for approximately 120-180 minutes or until they begin to firm. Time will vary depending upon substrate and ambient temperature.

CLEANING OF JOINTS:

Apply liberal amount of clean, cool water to the grouted area. Adding a few drops of dishwashing liquid to the water will aid in clean up. Using a soft sponge, work in a circular motion to loosen grout film and finish joints smoothly. If necessary add more

water to aid cleaning. Clean film from tile with a damp cotton towel and clean water. Change rinsed water frequently to aid cleanup and minimize grout residue left behind. Fingertip can be used to smoothen the joints but care to be taken because flush joint may not get while fingering over grouted joints. Final cleaning can be done on similar way after 24 hrs of first cleaning or after the grouts sets firmly. Time will vary depending upon substrate and ambient temperature. Do not do final cleaning before the grout joints sets firmly.

EASY MAINTENANCE:

Generally, light foot traffic can be allowed in 24 hours at 25°C, normal foot traffic in 36 hours and heavy foot traffic in 72 hours. Grouted area should be kept dry and protected from exposure to dust, dirt, food or other chemicals, that could stain or attack the grout and spoil the colour.

- Grout residue, or wash water will discolour painted or anodized surfaces upon contact.

LIMITATIONS:

- Should be tested for possible staining or slight colour changes when used with porous, absorptive, textured tile and stone units such as rough textured ceramic tile, natural stone or marble.
- Lower temperatures will cause the grout to become stiff and more difficult to work and will extend initial set. Higher temperatures will cause the grout to become pastier and will accelerate the set.
- Not recommended in some manufacturing facilities where heavy solvents are used. Consult Technical Services on questionable installations.
- Colours may be slightly different than shown on colour card or grout chart. When colour considerations are critical, a mock-up should be constructed prior to final selection and application.

PROTECTION OF JOB SITE:

Protect grouted are from contamination until it is fully cured. Avoid contact with eyes or skin. In case of contact, clean with plenty of water and seek medical attention. Use personal protective instruments such as gloves, goggles, aprons, masks, etc while handling the product and application of same

WARRANTY

Acrete Adhesions India Pvt Limited warrants to the original purchaser that its product shall be free from defects in material for a period of 3 years from the manufacturing of the product. Our sole liability under this warranty shall be limited to the replacement of our purchased product if proved defective under normal handling as stated in the TDS. This warranty will not extend to any other product or items which were handled along with our product. This warranty or any other legal issues or claims are subject to Mangalore jurisdiction only.

CUSTOMER SERVICE:

For any query related to product availability, cost, coverage, applicators, installation instructions, problems and trouble shooting, contact customer service executive on our 24 X 7 customer help line+91 963 260 5577 or write email to customercare@acebond.in
For product or other information, please write us to info@acebond.in
Visit us at www.acebond.in

DECLARATION:

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided since conditions of use, application method and surface preparation at site are beyond our control. All legal issues are subject to Mangalore jurisdiction only.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.