

PRODUCT TECHNICAL DATA SHEET







Ref: AAIPL/TDS/059-16 Rev: 02/05-16



Aceseal MRA is a high performance mould releasing agent manufactured by blending of superior quality minerals, releasing agents and additives which is having release properties that are superior to those of conventional mould oil. The chemicals react with alkali in the concrete to form a thin water repellent skin on the surface of the mould, thereby enabling easy striping from concrete and acting as a protection to steel and other form of mould or formwork. It is a clear free flow liquid that can be easily sprayed by spray gun or applied by cotton waste, brush or roller. It is suitable for use on metal, ply wood, timber, aluminium, plastic and all type of moulds.

- Easy to apply by brush or roller or spray
- Easy demoulding
- Provides high quality and sharp edge concrete
- Withstand 100*C temperature
- Can be used on all type of formwork
- Does not stain concrete and does not behave as bondbreaker while plastering on concrete
- Does not corrode steel or swell wooden mould

ADVANTAGES:



PRODUCT TECHNICAL DATA SHEET



APPLICATION

It is suitable for use on metal, ply wood, timber, aluminum, plastic and all type of moulds.

PACK SIZE:

Available in 5 ltr and 20 ltr pack

SHELF LIFE:

12 months if stored in cool and dry area in unopened container. Shelf life is calculated from the month of manufacturing of the product.

CAUTION:

- Store in cool and dry place.
- High temperature or moisture will affect the product.
- Once bottle is opened, then finish it off without keeping for long time.
- Avoid eye contact or prolonged contact with skin.
- Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes and consult a physician.
- Do not breathe directly; wear PPE whenever necessary

WARRANTY

Accrete adhesions India Private Limited warrants to the original purchaser that its product shall be free from defects in material for a period of one year from the manufacturing of the product. Our sole liability under this warranty shall be limited to the replacement of our purchased product if proved defective under normal handling as stated in the TDS. This warranty will not extend to any other product or items which were handled along with our product. This warranty or any other legal issues or claims are subject to Mangalore jurisdiction only.

CUSTOMER SERVICE:

For any query related to product availability, cost, coverage, applicators, installation instructions, problems and trouble shooting, contact customer service executive on our 24 X 7 customer help line +91 963 260 5577 or write email to customercare@acebond.in. For product or other information, please write us to info@acebond.in. Visit us at www.acebond.in.

DECLARATION:

The information and recommendations contained herein are based upon data believed to be correct; however, no guarantee or warranty of any kind expressed or implied is made with respect to the information provided since conditions of use, method of application and surface preparation at site are beyond our control. All legal issues are subject to Mangalore jurisdiction only.

NB: Technology may change with time necessitating changes to this Technical Data Sheet (TDS). It is the responsibility of the user to ensure that the latest TDS is being used.